

Halogenfree Self-Extinguishing Flexible Conduit With Guide Wire

Cable Clands

Corrugated Plastic Conduits & Fittings

Flexible Steel Conduits & Fittings

Residential Type Conduits & Fittings

Pre - Wired Conduits

Expandable Braided Sleeveings



TECHNICAL INFORMATION

MATERIAL : POLYPROPYLENE

STANDARD : EN 61386-22

OPERATING TEMPERATURE: -25C / +60C

FLAMMABILITY CLASS : UL94 V2

COLOR : GREY (RAL 7001) , BLACK (RAL 9005) , LIGHT GREY (RAL 7035)

COMPRESSION STRENGTH : LIGHT : 320N, MEDIUM : 750N, HEAVY : 1250N

PULL-OFF (TENSILE) STRENGTH : 500 N

CERTIFICATE : CE, ROHS

FEATURES

HALOGEN FREE | SULPHUR FREE | PHOSPHORUS FREE |
 SELF-EXTINGUISHING | UL94 V0 FLAME RETERDANCY | EASY
 INSTALLATION | BEST GRADE MATERIAL | RESISTANT TO ACID
 AND SOLVENT

APPLICATIONS

RESIDENTIAL BUILDING | COMMERCIAL BUILDINGS |
 INSIDE CONCRETE & OUTSIDE CONCRETE | UNDER
 FLOOR INSTALLATIONS

Light Serie 320 N

GREY CODE	BLACK CODE	LIGHT GREY CODE	SIZE	INSIDE DIA. (MM)	OUTSIDE DIA. (MM)	PACK QTY (M)
THYSK-116-G	THYSK-116-S	THYSK-116-LG	16 MM	11,70	16,0	100
THYSK-120-G	THYSK-120-S	THYSK-120-LG	20 MM	14,20	20,0	100
THYSK-125-G	THYSK-125-S	THYSK-125-LG	25 MM	18,10	25,0	50
THYSK-132-G	THYSK-132-S	THYSK-132-LG	32 MM	24,20	32,0	50
THYSK-140-G	THYSK-140-S	THYSK-140-LG	40 MM	31,2	40,0	50
THYSK-150-G	THYSK-150-S	THYSK-150-LG	50 MM	39,6	50,0	25

Medium Serie 750 N

GREY CODE	BLACK CODE	LIGHT GREY CODE	SIZE	INSIDE DIA. (MM)	OUTSIDE DIA. (MM)	PACK QTY (M)
THYSK-216-G	THYSK-216-S	THYSK-216-LG	16 MM	11,60	16,0	100
THYSK-220-G	THYSK-220-S	THYSK-220-LG	20 MM	14,10	20,0	100
THYSK-225-G	THYSK-225-S	THYSK-225-LG	25 MM	18,00	25,0	50
THYSK-232-G	THYSK-232-S	THYSK-232-LG	32 MM	24,10	32,0	50
THYSK-240-G	THYSK-240-S	THYSK-240-LG	40 MM	31,0	40,0	50
THYSK-250-G	THYSK-250-S	THYSK-250-LG	50 MM	39,3	50,0	25

Heavy Serie 1250 N

GREY CODE	BLACK CODE	LIGHT GREY CODE	SIZE	INSIDE DIA. (MM)	OUTSIDE DIA. (MM)	PACK QTY (M)
THYSK-316-G	THYSK-350-S	THYSK-316-LG	16 MM	11,40	16,0	100
THYSK-320-G	THYSK-320-S	THYSK-320-LG	20 MM	14,00	20,0	100
THYSK-325-G	THYSK-325-S	THYSK-325-LG	25 MM	17,70	25,0	50
THYSK-332-G	THYSK-332-S	THYSK-332-LG	32 MM	24,00	32,0	50
THYSK-340-G	THYSK-340-S	THYSK-340-LG	40 MM	30,80	40,0	50
THYSK-350-G	THYSK-350-S	THYSK-350-LG	50 MM	39,00	50,0	25