


Compression Fixed Connector Female Type



TECHNICAL INFORMATION

- CAP :** NICKEL PLATED BRASS (NPB)
- BODY :** NICKEL PLATED BRASS (NPB)
- STANDARD :** EN 62444 / 50262
- THREAD TYPE :** METRIC EN 60423 , PG DIN 40430 , NPT ANSI B1.20.1
- PROTECTION CLASS :** IP 67 / IP 68
- OPERATING TEMPERATURE:** -40°C / +120°C
- FLAMMABILITY CLASS :** UL94 V2
- COLOR :** SELF-COLOURED

FEATURES

- BEST GRADE MATERIAL | HIGH MECHANICAL STRENGTH
- WATERPROOF | VIBRATION RESISTANT

APPLICATIONS

- MACHINE BUILDINGS | AUTOMATION SYSTEMS
- CONSTRUCTION | MARINE , SHIPYARD

Metric Thread

CODE	THREAD SIZE	CONDUIT NOM. SIZE (MM)	TD (MM)	TL (MM)	SW BODY (MM)	SW CAP (MM)	H (MM)	QUANTITY (PC/ PACK)
BSMR-M12-F	M12X1,5	10,0	12,0	10,0	20,0	20,0	26,4	50
BSMR-M16S-F	M16X1,5	12,0	16,0	12,0	22,0	24,0	29,8	50
BSMR-M16-F	M16X1,5	16,0	16,0	12,0	24,0	26,0	33,0	50
BSMR-M20S-F	M20X1,5	16,0	20,0	12,0	24,0	26,0	33,5	50
BSMR-M20-F	M20X1,5	20,0	20,0	12,0	26,0	29,0	33,5	50
BSMR-M25-F	M25X1,5	25,0	25,0	14,0	33,0	35,0	40,5	25
BSMR-M32-F	M32X1,5	32,0	32,0	15,0	40,0	42,0	45,8	10
BSMR-M40-F	M40X1,5	40,0	40,0	16,0	54,0	53,0	47,5	5
BSMR-M50-F	M50X1,5	50,0	50,0	18,0	58,0	62,0	53,0	5
BSMR-M63-F	M63X1,5	65,0	63,0	20,0	72,0	76,0	58,8	4
BSMR-M75-F	M75X1,5	75,0	75,0	22,0	85,0	90,0	60,0	4

Pg Thread

CODE	THREAD SIZE	CONDUIT NOM. SIZE (MM)	TD (MM)	TL (MM)	SW BODY (MM)	SW CAP (MM)	H (MM)	QUANTITY (PC/ PACK)
BSPR-PG7-F	PG-7	10,0	12,5	10,0	20,0	20,0	26,4	50
BSPR-PG9-F	PG-9	12,0	15,2	12,0	22,0	24,0	29,8	50
BSPR-PG11/1-F	PG-11	16,0	18,6	12,0	24,0	26,0	33,0	50
BSPR-PG13-F	PG-13,5	16,0	20,4	12,0	26,0	26,0	33,5	50
BSPR-PG16-F	PG-16	20,0	22,5	12,0	26,0	29,0	33,5	50
BSPR-PG21-F	PG-21	25,0	28,3	14,0	33,0	35,0	40,5	25
BSPR-PG29-F	PG-29	32,0	37,0	15,0	44,0	42,0	45,8	10
BSPR-PG36-F	PG-36	40,0	47,0	16,0	52,0	52,0	47,5	5
BSPR-PG42-F	PG-42	50,0	54,0	18,0	60,0	58,0	53,0	5
BSPR-PG48-F	PG-48	63,0	59,3	20,0	72,0	70,0	58,8	4

Npt Thread

CODE	THREAD SIZE	CONDUIT NOM. SIZE (MM)	TD (MM)	TL (MM)	SW BODY (MM)	SW CAP (MM)	H (MM)	QUANTITY (PC/ PACK)
BSNR-3/8-F	3/8"	16,0	17,0	10,0	22,0	26,0	33,0	50
BSNR-1/2S-F	1/2"	16,0	21,3	12,0	24,0	26,0	33,0	50
BSNR-1/2-F	1/2"	20,0	21,3	12,0	26,0	29,0	33,5	50
BSNR-3/4-F	3/4"	25,0	26,6	12,0	33,0	35,0	40,5	25
BSNR-1-F	1"	32,0	33,4	14,0	40,0	42,0	45,8	10
BSNR-1 1/4-F	1 1/4"	40,0	42,0	16,0	50,0	52,0	47,5	5
BSNR-1 1/2-F	1 1/2"	50,0	48,2	18,0	58,0	58,0	53,0	5
BSNR-2-F	2"	63,0	60,3	20,0	70,0	70,0	58,8	4