

Halogenfree Self-Extinguishing Coil Pipe

Cable Clamps

Corrugated Plastic Conduits & Fittings

Flexible Steel Conduits & Fittings

Residential Type Conduits & Fittings

Pre - Wired Conduits

Expandable Braided Sleeving



TECHNICAL INFORMATION

MATERIAL : POLYETHYLENE

STANDARD : EN 61386-22

PROTECTION CLASS : IP 66 / IP 67 / IP 68

OPERATING TEMPERATURE: -25C / +60C

FLAMMABILITY CLASS : UL94 V0

COLOR : GREY (RAL 7001),BLACK (RAL 9005),LIGHT GREY (RAL 7035)

COMPRESSION STRENGTH : LIGHT: 320N,MEDIUM:750N,HEAVY:1250N

PULL-OFF (TENSILE) STRENGTH : 1000 N

CERTIFICATE : CE, ROHS

FEATURES

HALOGEN FREE | SULPHUR FREE | PHOSPHORUS FREE |
EASY INSTALLATION | BEST GRADE MATERIAL | RESISTANT
TO ACID AND SOLVENT

APPLICATIONS

RESIDENTIAL BUILDING | COMMERCIAL BUILDINGS |
INSIDE CONCRETE & OUTSIDE CONCRETE | UNDER
FLOOR INSTALLATIONS

Light Serie 320 N

ORANGE CODE	BLACK CODE	LIGHT GREY CODE	SIZE	INSIDE DIA. (MM)	OUTSIDE DIA. (MM)	PACK QTY (M)
THYK-116-O	THYK-116-S	THYK-116-LG	16 MM	11,70	16,0	100
THYK-120-O	THYK-120-S	THYK-120-LG	20 MM	14,20	20,0	100
THYK-125-O	THYK-125-S	THYK-125-LG	25 MM	18,10	25,0	50
THYK-132-O	THYK-132-S	THYK-132-LG	32 MM	24,20	32,0	50
THYK-140-O	THYK-140-S	THYK-140-LG	40 MM	31,2	40,0	50
THYK-150-G	THYK-150-S	THYK-150-LG	50 MM	39,6	50,0	25

Medium Serie 750 N

ORANGE CODE	BLACK CODE	LIGHT GREY CODE	SIZE	INSIDE DIA. (MM)	OUTSIDE DIA. (MM)	PACK QTY (M)
THYK-216-O	THYK-216-S	THYK-216-LG	16 MM	11,60	16,0	100
THYK-220-O	THYK-220-S	THYK-220-LG	20 MM	14,10	20,0	100
THYK-225-O	THYK-225-S	THYK-225-LG	25 MM	18,00	25,0	50
THYK-232-O	THYK-232-S	THYK-232-LG	32 MM	24,10	32,0	50
THYK-240-O	THYK-240-S	THYK-240-LG	40 MM	31,0	40,0	50
THYK-250-O	THYK-250-S	THYK-250-LG	50 MM	39,3	50,0	25

Heavy Serie 1250 N

ORANGE CODE	BLACK CODE	LIGHT GREY CODE	SIZE	INSIDE DIA. (MM)	OUTSIDE DIA. (MM)	PACK QTY (M)
THYK-316-O	THYK-350-S	THYK-316-LG	16 MM	11,40	16,0	100
THYK-320-O	THYK-320-S	THYK-320-LG	20 MM	14,00	20,0	100
THYK-325-O	THYS-325-S	THYK-325-LG	25 MM	17,70	25,0	50
THYK-332-O	THYK-332-S	THYK-332-LG	32 MM	24,00	32,0	50
THYK-340-O	THYK-340-S	THYK-340-LG	40 MM	30,80	40,0	50
THYK-350-O	THYK-350-S	THYK-350-LG	50 MM	39,00	50,0	25