


Nickel Plated Blind Stop



TECHNICAL INFORMATION

- MATERIAL :** NICKEL PLATED BRASS
- STANDARD :** EN 62444
- THREAD TYPE :** METRIC EN 60423 , PG DIN 40430
- PROTECTION CLASS :** IP 68 / 5 BAR
- OPERATING TEMPERATURE :** -30°C /+100°C
- FLAMMABILITY CLASS :** UL94V2
- COLOR :** SELF - COLOURED
- O-RING :** NBR
- CERTIFICATE :** CE, ROHS

FEATURES

HIGH MECHANICAL STRENGTH | EASY INSTALLATION | BEST GRADE MATERIAL


APPLICATIONS

WHERE TO NEED END ENTRIES

Metric Thread

CODE	SIZE	TD (MM)	TL (MM)	D (MM)	H (MM)	
TMK-01	M12X1,5	12,0	5,0	14,0	7,5	100
TMK-02	M16X1,5	16,0	5,0	18,0	8,0	100
TMK-03	M20X1,5	20,0	6,5	22,0	9,5	100
TMK-04	M25X1,5	25,0	7,0	28,0	11,0	100
TMK-05	M32X1,5	32,0	8,0	35,0	12,0	50
TMK-06	M40X1,5	40,0	8,5	44,0	13,0	50
TMK-07	M50X1,5	50,0	9,0	54,0	15,0	25
TMK-08	M63X1,5	63,0	10,0	67,0	16,0	10

PG Thread

CODE	SIZE	TD (MM)	TL (MM)	D (MM)	H (MM)	
TPK-01	PG-7	12,5	5,0	14,0	8,0	100
TPK-02	PG-9	15,2	6,0	17,0	9,0	100
TPK-03	PG-11	18,6	6,0	20,0	9,0	100
TPK-04	PG-13,5	20,4	6,5	22,0	9,5	100
TPK-05	PG-16	22,5	6,5	24,0	9,5	100
TPK-06	PG-21	28,3	7,0	30,0	11,0	50
TPK-07	PG-29	37,0	8,0	39,0	12,0	25
TPK-08	PG-36	47,0	9,0	50,0	15,0	10
TPK-09	PG-42	54,0	10,0	57,0	16,0	10
TPK-10	PG-48	59,3	10,0	64,0	16,0	10