



TECHNICAL INFORMATION

MATERIAL : NICKEL PLATED BRASS

STANDARD : EN 62444

THREAD TYPE : METRIC EN 60423 , PG DIN 40430, NPT ANSI B1.20.1


OPERATING TEMPERATURE : -30°C/+100°C


COLOR : SELF - COLOURED

CERTIFICATE : CE, ROHS

FEATURES

HIGH MECHANICAL STRENGTH | EASY INSTALLATION | BEST GRADE MATERIAL

		Metric Thread		
CODE	SIZE	SW (MM)	H (MM)	
TML-01	M12X1,5	15,0	2,8	50
TML-02	M16X1,5	19,0	3,0	50
TML-03	M20X1,5	24,0	3,5	50
TML-04	M25X1,5	30,0	4,0	25
TML-05	M32X1,5	36,0	5,0	25
TML-06	M40X1,5	46,0	5,0	20
TML-07	M50X1,5	60,0	5,0	15
TML-08	M63X1,5	70,0	6,0	12
TML-09	M72X1,5	77,0	7,0	4
TML-10	M75X1,5	80,0	7,0	4
TML-11	M80X1,5	90,0	8,0	2
TML-12	M90X1,5	100,0	8,0	2

		PG Thread		
CODE	SIZE	SW (MM)	H (MM)	
TSL-01	PG-7	15,0	2,8	50
TSL-02	PG-9	18,0	2,8	50
TSL-03	PG-11	21,0	3,0	50
TSL-04	PG-13,5	23,0	3,0	50
TSL-05	PG-16	26,0	3,0	25
TSL-06	PG-21	32,0	3,5	25
TSL-07	PG-29	41,0	4,0	20
TSL-08	PG-36	51,0	5,0	15
TSL-09	PG-42	60,0	5,0	12
TSL-10	PG-48	64,0	5,5	12