


Pre Wired Conduits With Antenna Cables Of Pvc Sheath



TECHNICAL INFORMATION

CONDUIT

MATERIAL : POLYPROPYLENE HALOGEN FREE

STANDARD : EN 61386-2

PROTECTION CLASS : IP68

OPERATING TEMPERATURE : -25C / +95C

FLAMMABILITY CLASS : UL94 V2

COLOUR : GREY (RAL 7001),LIGHT GREY (RAL 7035),ALTERNATE COLOURS AVAIL.

COMPRESSION STRENGTH : 750 N

CERTIFICATE : CE, ROHS

CABLE

INSULATION : PE

SHEATH : PVC

OPERATING TEMPERATURE : - 40 C - 70 C

TEST VOLTAGE (AC) : 3 KV

MIN. BENDING RADIUS : 10XD

OPERATING VOLTAGE : 1,3 K V

FLAME RETARDANCY TEST : IEC 60332-1/2

ADDITIONAL FEATURE : LEAD FREE

PRODUCT CODE	CONDUIT SIZE	CABLE COUNT & DIMENSION (mm2)	CABLE INSULATION	SHEATH	ROLL LENGTH (mt)*
FPW-RG6 16 R100	M16	RG6	PE	PVC	100

* ALTERNATE ROLL LENGTH AVAILABLE