

V0 Flame Retardant Polyester Pet Braided Sleeving



TECHNICAL INFORMATION

MATERIAL : POLYESTER (PET) V0

MONOFIL DIA : 0,22 MM , 0,25 MM

STANDARD : DIN 5510

CERTIFICATE : CE, ROHS

OPERATING TEMPERATURE: -50°C / +120°C (SHORT TERM +150C)

COLOR : GREY (RAL 7031) , BLACK (RAL 9011)

FLAMMABILITY CLASS : UL94 V0

FEATURES

BEST GRADE MATERIAL | HALOGEN FREE | SULPHUR FREE
 | PHOSPHORUS FREE | ABRASION RESISTANT | BENZINE |
 SOLVENT AND ACID RESISTANT | UL 94 V0 FLAME RETARDANCY
 | SELF-EXTINGUISH | HIGH MECHANICAL STRENGTH | EASY
 INSTALLATION | UV RESISTANT (BLACK COLOUR)

APPLICATIONS

MACHINE INDUSTRY | AUTOMATION SYSTEMS |
 AUTOMOTIVE | SOLAR SYSTEMS | CONSTRUCTION |
 ROBOT APPLICATIONS | SHIP INDUSTRY

BLACK CODE	GREY CODE	HOSE DIA.	MIN. EXPANSION DIA. (MM)	MAX. EXPANSION DIA. (MM)	REEL LENGTH (M)
AGRVO-5-S	AGRVO-5-G	5	3,0	8,0	100
AGRVO-8-S	AGRVO-8-G	8	5,0	16,0	100
AGRVO-10-S	AGRVO-10-G	10	7,0	14,0	100
AGRVO-12-S	AGRVO-12-G	12	8,0	24,0	100
AGRVO-15-S	AGRVO-15-G	15	11,0	20,0	100
AGRVO-20-S	AGRVO-20-G	20	19,0	28,0	100
AGRVO-25-S	AGRVO-25-G	25	21,0	34,0	50
AGRVO-30-S	AGRVO-30-G	30	25,0	40,0	50
AGRVO-40-S	AGRVO-40-G	40	31,0	55,0	50
AGRVO-50-S	AGRVO-50-G	50	40,0	68,0	50